Material Safety Data Sheet
May be used to comply with
OSHA's Hazard Communication Standard,
29 CFR 1910.1200. Standard must be consulted
for specific requirements.

U.S. Department of Labor
Occupational Safety and Health Administration
(Non-Mandatory Form)
Form Approved
OMB No. 1218-0072

IDENTITY (As Used on Label and List)

Bonide Japanese Beetle Killer RTU **I.D. NO. 4309**

Date: October 3 , 1998

Section I

Bonide Products, Inc. (800) 424-9300
2 Wurz Ave. (315) 736-8231
Yorkville, NY 13495

Section II - Hazardous Ingredients/Identity

Hazardous Components (Specific Chemical Identity: Common Name(s)	OSHA PEL	ACGIH TLV	Other Limits	% (Optional)
Pyrethrins				0.02
Piperonyl Butoxide 51-03-06				0.20

Section III - Fire/Explosion Hazard Data

FLASH POINT: N/A FLAMMABILITY: Puts out flame.
FIRE FIGHTING COMMENTS: Avoid use of water to reduce contamination hazard.
UNUSUAL FIRE/EXPLOSION HAZARD: None

Section IV - Spill or Leak Procedures

PRECAUTIONS:Avoid prolonged contact with spilled material.
DISPOSAL: Soak up with absorbent. Small spills may be placed in original container, wrapped in paper and placed in trash. For large spills, consult State and Local authorities for disposal directives.

Section V - Storage and Handling

STORAGE: Keep in a cool, dry place, and in an area inaccessible to children or pets. Avoid temperature extremes.
HANDLING PRECAUTIONS: Avoid contact with eyes, skin or clothing. Wash thoroughly after handling.
CONTAINER DISPOSAL: Wrap empty container and place in trash collection.

Section VI - Health Hazard Data

PRECAUTIONS:May be harmful if swallowed or absorbed through skin.
FIRST AID: IF IN EYES OR ON SKIN: Flush with plenty of water. Get medical attention if irritation persists.
NOTE TO PHYSICIAN: May cause allergic reactions in susceptible individuals.

Section VII - Additional Information/Hazards

This product is toxic to fish and other aquatic organisms. Do not contaminate water with this product.

KEEP OUT OF REACH OF CHILDREN

ABBREVIATION KEY

N/A: NOT AVAILABLE OR APPLICABLE N/E: NOT ESTABLISHED
TLV: THRESHOLD LIMIT VALUE TWA: TIME WEIGHTED AVG./8 HOUR WORKDAY
STEL: SHORT TERM EXPOSURE LIMIT D.O.T.: DEPARTMENT OF TRANSPORTATION

DISCLAIMER OF EXPRESSED AND IMPLIED WARRANTIES
Buyer assumes all risks of use, storage and handling of this material not in strict accordance with directions given herewith.